


The TITAN RS is a recessed mount fitting which is designed to be comfortable and durable but still withstand violence and rough weather conditions, the product is widely used in environments which are sensitive for molest. The TITAN serie is mainly used as the main lighting in underpasses, canopies and alleys.

CE

IP65

IK16



## Specifications

Housing material	Stainless steel
Surface finish	Powder coated
Cover material	Polycarbonate Structured
LED type	Bridgelux 2835 LED
CRI	≥ 90
Voltage	230 V
Lifetime fixture	30 years
Lifetime LED	L90B10 @ 100.000h, 25°C
Dimmable	DALI
Future proof	Yes
Net efficiency	160 Lumen/Watt



# LIGHT

INTERNATIONAL

Typenumber	Length	Lumen	Load	Weight
TRS3 1 3K	417mm	994 lm	6.2W	4.9 kg
TRS7 1 3K	759mm	1062 lm	6.2W	8.5kg
TRS7 2 3K	759mm	2133 lm	11.8W	8.5kg
TRS13 3 3K	1367mm	3212 lm	18.4W	14.8kg
TRS13 4 3K	1367mm	4228 lm	23.4W	14.8kg
TRS13 5 3K	1367mm	6473 lm	37.9W	14.8kg

Colour black (RAL 9005) Standard

Colour white (RAL 9016) Add W

Colour grey (RAL 7035) Add G

LED Colour temperature Replace 3K for 4K

Warranty 10 years

Country of origin The Netherlands

SROI > 25% of our production

Latest development 08/01/2024

LDT/IES file Download via website



**LIGHT**  
INTERNATIONAL

