

The TITAN SFL is a surface mount fitting which is designed to create a line of light with or without infill panels. A robust architectural line of light which still withstands violence and rough conditions. The TITAN serie is mainly used as the main lighting in underpasses, canopies and alleys.

IP65

IK16



Specifications

Housing material	Stainless steel and aluminium
Surface finish	Powder coated
Cover material	Polycarbonate Structured
LED type	Medium Power SMD LED
CRI	≥ 80
Voltage	230 V
Lifetime fixture	30 years
Lifetime LED	L90B10 @ 100.000h, 25°C
Dimmable	DALI
Future proof	Yes
LED efficiency	200 Lumen/Watt

 These specifications can be customized on request, please contact us for more information

Typenumber	Length	Lumen	Load	Weight
TSFL4 1 3K B	422mm	994 lm	6.2W	4.7 kg
TSFL8 1 3K B	767mm	1062 lm	6.2W	7.4kg
TSFL8 2 3K B	767mm	2133 lm	11.8W	7.4kg
TSFL14 3 3K B	1375mm	3212 lm	18.4W	14.5kg
TSFL14 4 3K B	1375mm	4228 lm	23.4W	14.5kg
TSFL14 5 3K B	1375mm	6473 lm	37.9W	14.5kg

Colour white (RAL 9005)	Standard (B)
Colour black (RAL 9016)	Replace B for W
Colour grey (RAL 7035)	Replace B for G
LED Colour temperature	Replace 3K for 4K
Customized product	Call us at +31-229-472011

Warranty	10 years
Country of origin	The Netherlands
SROI	> 25% of our production
Latest development	10/02/2022
LDT/IES file	Download via website

