

The TITAN SFL is a surface mount fitting which is designed to create a line of light with or without infill panels. A robust architectural line of light which still withstands violence and rough conditions. The TITAN serie is mainly used as the main lighting in underpasses, canopies and alleys.

CE

IP65

IK16



Specifications

| | |
|------------------|--------------------------|
| Housing material | Stainless steel |
| Surface finish | Powder coated |
| Cover material | Polycarbonate Structured |
| LED type | Bridgelux 2835 LED |
| CRI | ≥ 90 |
| Voltage | 230 V |
| Lifetime fixture | 30 years |
| Lifetime LED | L90B10 @ 100.000h, 25°C |
| Dimmable | DALI |
| Future proof | Yes |
| Net efficiency | 160 Lumen/Watt |



LIGHT

INTERNATIONAL

| Typenumber | Length | Lumen | Load | Weight |
|---------------|--------|---------|-------|--------|
| TSFL3 1 3K B | 422mm | 994 lm | 6.2W | 4.7 kg |
| TSFL7 1 3K B | 767mm | 1062 lm | 6.2W | 7.4kg |
| TSFL7 2 3K B | 767mm | 2133 lm | 11.8W | 7.4kg |
| TSFL13 3 3K B | 1375mm | 3212 lm | 18.4W | 14.5kg |
| TSFL13 4 3K B | 1375mm | 4228 lm | 23.4W | 14.5kg |
| TSFL13 5 3K B | 1375mm | 6473 lm | 37.9W | 14.5kg |

Colour black (RAL 9005) Standard (B)

Colour white (RAL 9016) Replace B for W

Colour grey (RAL 7035) Replace B for G

LED Colour temperature Replace 3K for 4K

Warranty 10 years

Country of origin The Netherlands

SROI > 25% of our production

Latest development 08/01/2024

LDT/IES file Download via website



LIGHT
INTERNATIONAL

