

The TITAN SQ is a surface mount fitting which is designed to be comfortable and durable but still withstand violence and rough weather conditions, the product is widely used in environments which are sensitive for molest. The TITAN serie is mainly used as the main lighting in underpasses, canopies and alleys.

CE

IP65

IK16



### Specifications

Housing material	Stainless steel
Surface finish	Powder coated
Cover material	Polycarbonate Structured
LED type	Bridgelux 2835 LED
CRI	≥ 90
Voltage	230 V
Lifetime fixture	30 years
Lifetime LED	L90B10 @ 100.000h, 25°C
Dimmable	DALI
Future proof	Yes
Net efficiency	160 Lumen/Watt



# LIGHT

INTERNATIONAL

Typenumber	Length	Lumen	Load	Weight
TSQ3 1 3K	378mm	994 lm	6.2W	4.5 kg
TSQ7 1 3K	722mm	1062 lm	6.2W	7.8kg
TSQ7 2 3K	722mm	2133 lm	11.8W	7.8kg
TSQ13 3 3K	1330mm	3212 lm	18.4W	14kg
TSQ13 4 3K	1330mm	4228 lm	23.4W	14kg
TSQ13 5 3K	1330mm	6473 lm	37.9W	14kg

Colour black (RAL 9005) Standard

Colour white (RAL 9016) Add W

Colour grey (RAL 7035) Add G

LED Colour temperature Replace 3K for 4K

Warranty 10 years

Country of origin The Netherlands

SROI > 25% of our production

Latest development 08/01/2024

LDT/IES file Download via website



**LIGHT**  
INTERNATIONAL

