

The TUBO75 is a ceiling or suspended mounted fitting which is designed to be comfortable and durable but still withstand violence, rough environmental and chemical conditions, the product is widely used in applications like livestock, carwashing, maritime, industrial and the food industry.

IP69

IK10



Specifications

Housing material	Stainless steel 316L and aluminium
Surface finish	-
Cover material	Opal (70% lt.)
LED type	Medium Power SMD LED
CRI	≥ 80
Voltage	230 V
Lifetime fixture	20 years
Lifetime LED	L90B10 @ 80.000h, 25°C
Dimmable	None DALI
Future proof	Yes
LED efficiency	200 Lumen/Watt

 These specifications can be customized on request, please contact us for more information

Typenumber	Length	Lumen	Load	Weight
TU755 1 3K S	552mm	1100 lm	7.9W	1.3kg
TU755 2 3K S	522mm	2200 lm	15.6W	1.3kg
TU7511 2 3K S	1152mm	2200 lm	11.8W	2.2kg
TU7511 3 3K S	1152mm	4400 lm	25.9W	2.2kg
TU7511 4 3K S	1152mm	6000 lm	40W	2.2kg

Suspension mount	Standard (S)
Ceiling/wall mount	Replace S for C
Customized mount	Contact our own workshop (Studio-CSP)
LED Colour temperature	Replace 3K for 4K
DALI dimmable	Add DA
Nightlight (2W)	Add NL
Customized product	Contact us, +31299472011

Warranty	10 years
Country of origin	The Netherlands
SROI	> 25% of our production
Latest development	10/02/2022
LDT/IES file	Download via website

