

CE

IP65

IK16

The VARO RS is an impact-resistant LED fitting, optionally available with an emergency light and 2W nightlight. Ideally suited for vandal-sensitive areas such as penitentiaries, correctional facilities, forensic psychiatric centers, other detention centers, medical centers and hospitals.



Specifications

Housing material	Stainless steel
Surface finish	Powder coated
Cover material	PET-G
LED type	Samsung LM561C, S6
Lifetime LED	L90B10 @ 100.000h, 25°C
Lifetime fixture	30 years
Voltage	230 V
CRI	≥ 80
Dimmable	DALI
Future proof	Yes
Net efficiency	112 Lumen/Watt



LIGHT
INTERNATIONAL

Typenumber	Lumen	Load	Weight
VARS1 3K W	800lm	7,1W	4,5kg
VARS2 3K W	1230lm	11W	4,5kg
VARS3 3K W	1714lm	16,4W	4,5kg

Colour white (RAL 9016)	Standard (W)
Colour black (RAL 9005)	Replace W for B
Colour grey (RAL 7035)	Replace W for G
LED Colour temperature	Replace 3K for 4K
Night light	Add NL
Emergency pack	Add EM
Customized product	Call: +31299-472011

Country of origin	The Netherlands
SROI	> 25% of our production
Latest development	10/08/2022
LDT/IES file	Download via website



LIGHT
INTERNATIONAL

