

Power Stripelite RS

RECESSED MOUNTED

The Power Stripelite RS is a fitting which is designed to be comfortable but still withstand violence, The fixture is widely used in environments where vandalism is prevalent.

The Power Stripelite is mainly used as the main lighting in tunnels, underpasses and canopies. With the Power Stripelite it is possible to achieve a vandal-resistant line of light.

CE

IP67

IK16



Specifications

Housing material	Stainless steel
Surface finish	Powder coated
Cover material	Acrylic opal (75% lt.)
LED type	Bridgelux 2835 LED
CRI	≥ 90
Voltage	230 V
Lifetime fixture	30 years
Lifetime LED	L90B10 @ 100.000h, 25°C
Dimmable	DALI
Future proof	Yes
Net efficiency	148 Lumen/Watt

Typenumber	Length	Lumen	Load	Weight
PSLRS6 1 3K	625mm	1.155 lm	7.8W	4kg
PSLRS6 R 3K	625mm	On request		4kg
PSLRS9 2 3K	925mm	1.740 lm	12W	6kg
PSLRS9 R 3K	925mm	On request		6kg
PSLRS12 3 3K	1225mm	2.260 lm	15.9W	8kg
PSLRS12 R 3K	1225mm	On request		8kg
PSLRS15 4 3K	1525mm	2.940 lm	20W	10kg
PSLRS15 R 3K	1525mm	On request		10kg

Colour none	Standard
Colour black (RAL 9005)	Add B
Colour white (RAL 9016)	Add W
Colour grey (RAL 7035)	Add G
LED Colour temperature	Replace 3K for 4K

Warranty	10 years
Country of origin	the Netherlands
SROI	> 25% of our production
Latest development	08/01/2024
LDT/IES file	Download via website

